Application No.: Not yet assigned Attorney Docket No. 07040.0216.00000 Preliminary Amendment—Filed April 6, 2005

# **Amendments to the Specification**

Please amend the specification, as follows:

Page 1, lines 1-2, replace the title paragraph with the following amended paragraph:

# [[A]] METHOD OF AND [[AN]] APPARATUS FOR ASSEMBLING TYRES FOR VEHICLE WHEELS

Page 1, line 4, delete the paragraph "Description" in its entirety:

Page 1, line 5, add the following paragraph in the form of a section heading after the title "METHOD OF AND APPARATUS FOR ASSEMBLING TYRES FOR VEHICLE WHEELS" and prior to the paragraph beginning "The present invention relates to a method . . . ."

### CROSS-REFERENCE TO RELATED APPLICATIONS

Page 1, line 5, add the following new paragraph after the heading "CROSS-REFERENCE TO RELATED APPLICATIONS" added above and prior to the paragraph beginning "The present invention relates to a method . . . ."

This application is a national-phase entry under 35 U.S.C. § 371 from International Application No. PCT/IT2003/000669, filed October 30, 2003, in the Italian Patent Office, the

Application No.: Not yet assigned Attorney Docket No. 07040.0216.00000

Preliminary Amendment—Filed April 6, 2005

content of which is relied upon and incorporated herein by reference. Additionally, Applicant

claim the right of priority under 35 U.S.C. § 119(a) - (d) based on International Application

No. PCT/IT02/00698, filed November 5, 2002, in the Italian Patent Office.

Page 1, line 5, add the following new paragraph in the form of a section heading after the

cross-reference to related applications added above and prior to the start of the paragraph

beginning "The present invention relates to a method . . . ."

BACKGROUND OF THE INVENTION

Page 1, line 5, add the following new paragraph in the form of a section subheading after

the heading "BACKGROUND OF THE INVENTION" added above and prior to the start of the

paragraph beginning "The present invention relates to a method . . . ."

Field of the Invention

Page 1, line 11, add the following new paragraph in the form of a section subheading

prior to the start of the paragraph beginning "A tyre for vehicle wheels generally . . . . "

Description of the Related Art

- 3 -

Application No.: Not yet assigned Attorney Docket No. 07040.0216.00000 Preliminary Amendment—Filed April 6, 2005

Page 5, line 19, add the following new paragraph in the form of a section heading prior to the start of the paragraph beginning "In accordance with the present invention . . . ."

#### SUMMARY OF THE INVENTION

Page 8, line 19, add the following new paragraph in the form of a section heading prior to the start of the paragraph beginning "Further features and advantages . . . ."

## BRIEF DESCRIPTION OF THE DRAWINGS

Page 9, line 11, add the following new paragraph in the form of a section heading prior to the start of the paragraph beginning "Referring particularly to Figs. 1 to 4 . . . ."

#### DETAILED DESCRIPTION OF THE EXEMPLARY EMBODIMENTS

Add a new page 34 after the claims, adding the following ABSTRACT OF THE DISCLOSURE. A new, separate page 34 including the ABSTRACT OF THE DISCLOSURE is enclosed.

#### ABSTRACT OF THE DISCLOSURE

A method of assembling tyres for vehicle wheels includes disposing a carcass structure on a primary drum, disposing a belt structure on an auxiliary drum, picking up the belt structure

Application No.: Not yet assigned Attorney Docket No. 07040.0216.00000 Preliminary Amendment—Filed April 6, 2005

from the auxiliary drum to transfer the belt structure to a position coaxially centered with respect to the carcass structure, shaping the carcass structure, applying a tread band, and applying a pair of sidewalls. At least one of applying the tread band and pair of sidewalls is carried out by winding up at least one continuous strip element of elastomer material in contiguous circumferential coils around the carcass structure. An apparatus for assembling tyres for vehicle wheels includes at least one primary drum, the auxiliary drum, a transfer member, at least one unit for applying the tread band onto the belt structure, and at least one unit for applying the pair of sidewalls against lateral walls of the carcass structure.